


Name of the Work: Estimate for Providing Lighting to Auditorium at Alliance Francaise de Bangalore premises, Vasanthnagar, Bangalore -52.

Sl. No	Device Description	Unit	Qty	Unit Price in INR	Amount in INR
	<b>CABLES &amp; CONDUITS</b>				
1	LIGHTING POINTS: Supply of 1.5sqmm 3core multistrand flexible cable As per ISI standards. Make-Lapp/Finolex	Mtr	1200		
2	LIGHTING POINTS: Supply of Conduits of 60mm x 60mm As per ISI standards (Cable tray from Light Points to Control Room).	Mtr	200		
3	Site of multistrand signal cable as per USITT standards Belden/Krystal	Mtr	150		
4	Installation Testing & commissioning of Cables, conduits & Gang boxes ( Labour Charges for the above mentioned tasks from 1 to 4 of this table as per approved SR rates calculated per meter.	Mtr	1500		
5	Supply of Ms Fabricated Gang Box with 2in1 IEC connectors 10amp capacity as per standards, Mat Black finish. (2 ports x 30 Gang Box = 60 Light Points). <ul style="list-style-type: none"> <li>As per the design suggested by the consultant these light points are designed for the stage as back lights, lighting bars 1 and 2, cross light ladders in 1<sup>st</sup> wing and 2<sup>nd</sup> wing of the stage, cyclorama wash and the FOH.</li> </ul>	Mtr	30		
	<b>ACCESSORIES FOR THE EXISTING LIGHT FIXTURES.</b>				
6	PAR 64 LAMP 1000w-240v Cieleed beam lamp 3200k Intensity controllable via dimmer circuits, Make-OSRAM / PHILIPS	No's	6		
7	SPOTLIGHT LAMP: 1000w-240v Single ended bipin lamp 3200k Intensity controllable via dimmer circuits, Make-OSRAM / PHILIPS	No's	6		
	<b>CONTROL ROOM EQUIPMENTS</b>				
8	DMX AMPLIFIER 1 inn 4 out Dmx signal booster, Signal inn & through: 3 pin male/female XRL. Power Input: AC 90-230V mensions(mm):500mmX183mmX85mm Net Weight: 2.0Kg Brand-I clair lighting.	No's	1		
9	RACK MOUNT DIMMER 10amp per Dimmer circuits. 12 Circuits Per Dimmer Pack. DMX512/1990 Standard. Power out via IEC connectors, Signal Via: 3 pole connectors. Net Weight: 13.0Kg Brand-I Clair lighting	No's	1		
10	DMX Controller DMX512/1990 Standard. upto 1024 channels 16 slider for manual control of channels DMX In/out: 3 pin male/female XRL. Power Input: DC 9-12V 500ma min Dimensions(mm):500mmX183mmX85mm Net Weight: 8.0Kg	No's	1		



General Secretary





Consultant

LED LIGHT FIXTURE					
11	LED LINEAR WASH : 4w Quad Led's RGB & Amber, Specially designed diffused lens kit for assymitric light distrubution, 60° opening angle, DmX 512 dimming with 4-8 Channel, Powder coated Black finish housing, IP20. Illuminates the whole stage area with uniform light spread. Brand-clair lighting.	No's	4		
12	LED PAR RGB : SW X 9 Quad Led RGB & Ww Opening Angle 25°. DmX 512 dimming with 4/5 Channel, Powder coated Black finish housing, IP20 protection having Sound Control & Master Slave Auto Run Mode, Illuminate the Indoor stage with uniformity. Brand-clair lighting.	No's	10		
13	LED PROFILE SPOT LIGHT : 160w Led Engine, 4way stainless steel for beam shaping, Beam angle 25°-50°. DmX 512 dimming with 2/3 Channel, Black finish housing, IP20. Illuminates the key presenter on the stage. Brand- I clair lighting.	No's	6		
MOUNTING ACCESSORIES					
14	Customized Mouting clamp for suspending light figures on source bars/Truss, made up of Aluminium or MS material with black powder coating matt black finish. Brand-RW	No's	30		
15	safety chain made up of GI wire rope bundled and twisted together having load bearing capacity of 25Kgs, sleve on the rope.Brand- I clair	No's	30		
16	Technical Coordination and supervision of safety standards, efficiency and installation.	No's	1		



General Secretary  
Alliance Francaise de Bangalore

Consultant